

Pharmacy Refrigerator

HYC-390



Frequency Conversion Energy Saving

Variable frequency compressor with optimized cooling system, more energy efficient.



Environmentally Friendly

Hydrocarbon compressor and refrigerant, the refrigerant does not contain any fluorine or chlorine which is super friendly to the environment.



Large Space, Superior Uniformity

The space is efficiently used, and the utilization rate is high and the temperature uniformity is $\pm 3^{\circ}\text{C}$.



Low Noise

Optimized system and noise reduction design to reduce the noise level to 43dB(A) (220V/50Hz).



Stable performance, multiple alarm modes

Three alarm modes (light, sound, remote); six types of alarm.



Microprocessor Control System



Self Closing Door with 90° Stay Open Feature



Precise Temperature Control



Security lock



Optional USB and Printer

Qingdao Haier Biomedical Co.,Ltd.

No.280 Feng Yuan Road, High-tech Zone,
Qingdao, 266109, P.R. China
Tel: +86-0532-88935593
Website: www.haiermedical.com



Haier Biomedical
International



Haier Biomedical
International



@haiermedicalint



Haier Biomedical
International



Haier Biomedical
International

Scope of Application



This product is suitable for pharmacy, pharmaceutical manufacturers, anti-epidemic stations, health centers and hospitals as key examples, which is used to store biological products and articles that need to be stored at 2~8°C.

Specifications



HYC-390

Technical Data

Cabinet Type	Upright, glass door	
Climate Class	N	
Cooling Type	Forced air cooling	
Defrost Mode	Auto	
Refrigerant	HC	
Noise (dB (A))	43	43

Performance

Temp Range (°C)	2~8	
-----------------	-----	--

Control

Controller	Microprocessor	
Display	LED	

Electrical Data

Power Supply (V/Hz)	220~240/50&60	115/60
Power (W)	360	240
Electrical Current (A)	1.8	2.4

Dimensions

Capacity (L/Cu.Ft)	390/13.8	
Net/Gross Weight (approx)	(kg)	116/139
	(lbs)	255.8/306.6
Interior Dimension (W*D*H)	(mm)	530*555*1380
	(in)	20.9*21.9*54.3
Exterior Dimension (W*D*H)	(mm)	665*710*1965
	(in)	26.2*28.0*77.4
Packing Dimension (W*D*H)	(mm)	690*790*2110
	(in)	27.1*31.0*82.9
Container Load (20'/40'/40'H)	22/44/44	



Accessories

Caster	Y	
Foot	Y	
Porthole	Y	
Shelves/Drawers	7/-	
USB Interface	Optional	Y
Temperature Recorder	Optional	

Alarms

High/Low Temp	Y	
Remote System	Y	
Power Failure	Y	
Sensor Error	Y	
Low Battery	Y	
Door Ajar	Y	

Other

Certificate	CE	UL
-------------	----	----